# HANSA Safety valve KSV 8.0 bar | 12.5 mm | G1/2''_2442080050




## Product short description:

Safety valve KSV 8.0 bar | 12.5 mm | G1/2''

Dimension (LxWxH): 48x41x131 mm
Weight: 0,49 kg
Part-No.: 2442080050

Made in Germany

## Product codes:

Reference: 2442080050
EAN13: 4251692918449

## Product description:

| | |
|---|---|
| Design type | direct acting spring loaded valves |
| Opening characteristic | Standard safety valve |
| Type designation | KSV and HD-KSV |
| Part number KSV | 2442xxx050 (xxx = bar value e.g. 280 = 28,0 bar) |
| Part number HD-KSV | 2443xxx050 (xxx = bar value e.g. 280 = 28,0 bar) |
| Valve size | DN 15 |
| threat | G 1/2" |
| outlet | G 1'' |
| overall length | 131 mm |
| | 27 |
| Weight pc | 0,490 kg |
| Licensing | Type tested safety valve (Modul B) |
| | Individual approval is based on |

Hansa Kältetechnik GmbH
Langenwiedenweg 111
D-59457 Werl / Deutschland
Telefon: +49 2922 86665-0
Fax: +49 2922 86665-284
E-Mail: info@hansakaelte.de

© 2024 HANSA Kältetechnik GmbH

| | |
|---|---|
| | Module F (2014/68 EU)<br>Z-D-002-11018/16 and Z-D-002-11020/16 |
| Marking KSV | SV · 16-11018 · 123 · D/G · 0,51 · p |
| Marking HD-KSV | SV · 16-11020 · 123 · D/G · 0,51 · P |
| Conformity assessment | Category IV - Modul B+F (2014/68 EU) |
| Applied standards and technical specification | DIN EN 378, AD 2000-Information Sheet, VdTÜV-Information Sheet, DIN EN ISO 4126-1, Guideline 2014/68 EU |
| Suitable for | Fluids in group 1 (please consult manufacturer) and 2<br>for all common refrigerants like HFC and CFC<br>Includes refrigeration fluids safety class A2L<br>"PRO" version for R290 Propan available.<br>Except NH3 refrigerant ! |
| Permissible temperature range | -30°C bis 120°C |
| Nominal Opening Pressure | as per catalogue ± 3% (EN ISO 4126-1 7.2.1) |
| Opening Pressure Diff | ≤ 10%, min. 0,1bar |
| | EN ISO 4126–1 Travel ° ≤ 0,26 |
| Threaded connection | G 1/2" |
| Max flow diameter | 12,5mm |
| Housing material | brass CW617N (2.402 or CuZn40Pb2) |
| Output | G 1" free blow-off |
| Reduced discharge coefficient | 0.51 |
| Remarks: | Each valve tested and controled under supervision of DEKRA quality control |

Hansa Kältetechnik GmbH
Langenwiedenweg 111
D-59457 Werl / Deutschland
Telefon: +49 2922 86665-0
Fax: +49 2922 86665-284
E-Mail: info@hansakaelte.de

© 2024 HANSA Kältetechnik GmbH

certificate with control number
attached to each valve

**Product features:**

Authorised refrigerants: R402A
Authorised refrigerants: R452C
Authorised refrigerants: R410B
Authorised refrigerants: R514A
Authorised refrigerants: R424A
Authorised refrigerants: R402B
Authorised refrigerants: R452A
Authorised refrigerants: R414A
Authorised refrigerants: R515A
Authorised refrigerants: R425A
Authorised refrigerants: R403A
Authorised refrigerants: R453A
Authorised refrigerants: R414B
Authorised refrigerants: R744
Authorised refrigerants: R426A
Authorised refrigerants: R407H
Authorised refrigerants: R456A
Authorised refrigerants: R416A
Authorised refrigerants: R1233zd(E)
Authorised refrigerants: R427A
Authorised refrigerants: R407I
Authorised refrigerants: R458A
Authorised refrigerants: R417A
Authorised refrigerants: R1234ze(E)
Authorised refrigerants: R427B
Authorised refrigerants: R428A
Authorised refrigerants: R407A
Authorised refrigerants: R460A
Authorised refrigerants: R417B
Authorised refrigerants: R1336mzz(E)
Authorised refrigerants: R434A
Authorised refrigerants: R407B
Authorised refrigerants: R460B
Authorised refrigerants: R417C
Authorised refrigerants: R1336mzz(Z)
Authorised refrigerants: R437A

Hansa Kältetechnik GmbH
Langenwiedenweg 111
D-59457 Werl / Deutschland
Telefon: +49 2922 86665-0
Fax: +49 2922 86665-284
E-Mail: info@hansakaelte.de

© 2024 HANSA Kältetechnik GmbH


Authorised refrigerants: R407C
Authorised refrigerants: R460C
Authorised refrigerants: R420A
Authorised refrigerants: R455A
Authorised refrigerants: R134a
Authorised refrigerants: R438A
Authorised refrigerants: R407D
Authorised refrigerants: R461A
Authorised refrigerants: R421A
Authorised refrigerants: R454C
Authorised refrigerants: R22
Authorised refrigerants: R442A
Authorised refrigerants: R407E
Authorised refrigerants: R463A
Authorised refrigerants: R421B
Authorised refrigerants: R2910
Authorised refrigerants: R30
Authorised refrigerants: R123
Authorised refrigerants: R448A
Authorised refrigerants: R407F
Authorised refrigerants: R464A
Authorised refrigerants: R422A
Authorised refrigerants: R124
Authorised refrigerants: R449B
Authorised refrigerants: R407G
Authorised refrigerants: R466A
Authorised refrigerants: R422B
Authorised refrigerants: R245fa
Authorised refrigerants: R449C
Authorised refrigerants: R408A
Authorised refrigerants: R468A
Authorised refrigerants: R422C
Authorised refrigerants: R401B
Authorised refrigerants: R449A
Authorised refrigerants: R409A
Authorised refrigerants: R471A
Authorised refrigerants: R422D
Authorised refrigerants: R401C
Authorised refrigerants: R450A
Authorised refrigerants: R409B
Authorised refrigerants: R513B
Authorised refrigerants: R422E
Authorised refrigerants: R401A

Hansa Kältetechnik GmbH
Langenwiedenweg 111
D-59457 Werl / Deutschland
Telefon: +49 2922 86665-0
Fax: +49 2922 86665-284
E-Mail: info@hansakaelte.de

© 2024 HANSA Kältetechnik GmbH

Authorised refrigerants: R452B
Authorised refrigerants: R410A
Authorised refrigerants: R513A
Authorised refrigerants: R423A

**Product attributes:**




Hansa Kältetechnik GmbH
Langenwiedenweg 111
D-59457 Werl / Deutschland
Telefon: +49 2922 86665-0
Fax: +49 2922 86665-284
E-Mail: info@hansakaelte.de

© 2024 HANSA Kältetechnik GmbH

Hansa Kältetechnik GmbH
Langenwiedenweg 111
D-59457 Werl / Deutschland

Telefon: +49 2922 86665-0
Fax: +49 2922 86665-284
E-Mail: info@hansakaelte.de

© 2024 HANSA Kältetechnik GmbH