HANSA Union nut DIN 8912 12 mm | 3/4''_2605111050



Product short description:

Union nut DIN 8912 12 mm | 3/4''
Manufactured from hot-pressed brass blanks for high gas tightness and safe installation and use at varying temperatures. Proven and reliable quality for refrigeration engineering.
Complies with DIN 8912 - meets DIN EN ISO14903 (frost proof)
Dimension (LxWxH): 24x28x20 mm
Weight: 0,055 kg
Part-No.: 2605111050

Product codes:

Reference: 2605111050
EAN13: 4251692913284

Product description:

Material: brass CW614N/617N (acc DIN EN12164)
Operating pressure rang up to 140bar
Operating temperature: -100°C to +200°C
Approved refrigerants: HFC / PFC / CFC / HC / R290 / R744
with the exception of NH3 containing refrigerants.
Approved oils: PAG / POE
Meets the requirements of DIN EN ISO 14903 point 7.8 "Frost test".

Product features:

Material design: Brass
Connection type: Flare
Connection: 3/4''-16UNF
Width across flats AF: 27
Pressure range: 140 bar

Hansa Kältetechnik GmbH
Langenwiedenweg 111
D-59457 Werl / Deutschland
Telefon: +49 2922 86665-0
Fax: +49 2922 86665-284
E-Mail: info@hansakaelte.de

© 2024 HANSA Kältetechnik GmbH

Fits: 1/2''
Fits: Ø 12mm

Product attributes:

Hansa Kältetechnik GmbH
Langenwiedenweg 111
D-59457 Werl / Deutschland
Telefon: +49 2922 86665-0
Fax: +49 2922 86665-284
E-Mail: info@hansakaelte.de

© 2024 HANSA Kältetechnik GmbH

Hansa Kältetechnik GmbH
Langenwiedenweg 111
D-59457 Werl / Deutschland

Telefon: +49 2922 86665-0
Fax: +49 2922 86665-284
E-Mail: info@hansakaelte.de

© 2024 HANSA Kältetechnik GmbH

Hansa Kältetechnik GmbH
Langenwiedenweg 111
D-59457 Werl / Deutschland

Telefon: +49 2922 86665-0
Fax: +49 2922 86665-284
E-Mail: info@hansakaelte.de

© 2024 HANSA Kältetechnik GmbH