

HANSA Shut-off ball valve HP 10 mm (120 bar) w access point KAV 2273410050

HANSA Kugelabsperrventile Symbolfoto
HANSA shutoff valves placeholder



Product short description:

Shut-off ball valve HP 10 mm (120 bar) w access point

Dimension (LxWxH): 132x13x51 mm

Weight: 0,29 kg

Part-No.: 2273410050

Product codes:

Reference: 2273410050

EAN13: 4251692910658

Product description:

"Bi-flow" design

Advantages

- Bi-flow, i.e. any mounting, independent of the direction of flow
- Sealing of the ball with 2 PTFE (Teflon) sleeves
- Suitable for use in liquid, suction and hot gas lines as well as in oil-free applications
- Marking on the spindle valve position (open or closed) (relief hole must point against the direction of flow)
- Maximum flow rate
- Sealable valve cap
- Bracket with screws included
- Also available with filling valve / sensor connection

Technical information

- Valve body material: brass
- Material of connection pipes: copper CU-DHP or K65 for 120 bar valves
- Approved refrigerants:
- HFC / PFC (e.g. R32) / CFC / HC / HFO (e.g. R1234ze, R454c) or blends like e.g. R407x oder R410x / R744
- R290 on request
- Refrigerants containing NH3 are not permitted!
- Maximum permissible operating pressure up to 120 bar (for details see table on page 2)

- Temperature resistance from - 40°C to + 155°C

Product features:

Product attributes:

