

## HANSA Filter drier sight glass combination with indicator flare connection HM165 15/16 mm | 5/8" \_2838816050

### Product short description:

Filter drier sight glass combination with indicator flare connection HM165 15/16 mm | 5/8"  
60 bar  
Dimension (LxWxH): xx mm  
Weight: 1,001 kg  
Part-No.: 2838816050

Made in Germany

### Product codes:

Reference: 2838816050  
EAN13: 4251692915837

### Product description:

Multiplex sight glass combi with indicator

Filter drier for liquid refrigerants, optimum mixture of molecular sieve and activated aluminium oxide

Technical details of the filter drier:

- Temperature range: -40°C +120°C
- Max. operating pressure: 60 bar
- High water absorption capacity
- High acid absorption capacity
- Ultra-fine filtration up to 15 micron
- Steel housing
- Closed design
- 3-fold filtration through granulate block, filter fleece and brass mesh filter
- CE marking according to PED 97/23 EC not required
- R290 Propane suitable: yes
- R744 CO2 suitable: yes

Approved refrigerants: HFC / PFC / CFC / HC / R744 / R290

---

except of NH<sub>3</sub> containing refrigerants.

Sight glass housing material: brass (acc DIN EN12164)

Typ FI: Indicates the lack of cooling agent in the refrigeration system plus a warning for moisture in the refrigerant. Large visible surface in all versions.

## **Product features:**

## **Product attributes:**



