

HANSA Filter drier sight glass combination with indicator of O-ring HM305 16 mm | 5/8" _2838840050



Product short description:

Filter drier sight glass combination with indicator of O-ring HM305 16 mm | 5/8" 55 bar

Dimension (LxWxH): xx mm

Weight: 1,05 kg

Part-No.: 2838840050

Made in Germany

Product codes:

Reference: 2838840050

EAN13: 4251692916018

Product description:

Multiplex sight glass combi with indicator

Filter drier for liquid refrigerants, optimum mixture of molecular sieve and activated aluminium oxide

Technical details of the filter drier:

- Temperature range: -40°C +120°C
- Max. operating pressure: 55 bar
- High water absorption capacity
- High acid absorption capacity
- Ultra-fine filtration up to 15 micron
- Steel housing
- Closed design
- 3-fold filtration through granulate block, filter fleece and brass mesh filter
- CE marking according to PED 97/23 EC not required
- R290 Propane suitable: yes
- R744 CO2 suitable: yes

Approved refrigerants: HFC / PFC / CFC / HC / R744 / R290
except of NH3 containing refrigerants.

Sight glass housing material: brass (acc DIN EN12164)

Typ FI: Indicates the lack of cooling agent in the refrigeration system plus a warning for moisture in the refrigerant. Large visible surface in all versions.

Product features:

Product attributes:

